



RESILIENT SUPPRESSORS

JESSIE'S GIRL SAFETY MANUAL

Warning

Before cleaning, installing or uninstalling your suppressor, verify that the magazine is out of the firearm and that the firearm is unloaded. Failure to do so, may result in serious injury or death. Your suppressor will become hot while in use, when installing or uninstalling the suppressor use the proper protective gear. Place the suppressor in an area where it will not come in contact with flammable material. Verify bore alignment prior to use. This suppressor has caliber and barrel length restrictions, failure to follow these restrictions will void your warranty and may lead to serious injury or death.

- Verify bore alignment prior to use.
- Ensure that the suppressor is always well tightened.
- Failure to follow caliber restrictions will void your warranty.

Cleaning

This suppressor can fully disassemble, which results in easy cleaning. At any time you feel your suppressor needs to be cleaned, remove the suppressor from the unloaded firearm, remove the flash hider end cap, and then gently push the baffle stack out of the rear of the suppressor with a small dowel rod. You can then clean the baffles by either using a CLR and water 50/50 mixture (soak overnight) or by using an ultrasonic cleaner with a non harsh cleaning solution. As far as the tube and the endcap we recommend you use a small plastic bristle brush to remove any carbon build up with any typical CLP or Gun oil.

Restrictions

- No barrel restrictions
- Full Auto Rated - 22LR & 5.7x28
- This suppressor is not rated for high pressure rifle rounds.

Contact us at info@resilientsuppressors.com if your caliber is not specified or you have any questions.