



## ***RESILIENT SUPPRESSORS*** ***JOLENE SAFETY MANUAL***

### **Warning**

Before cleaning, installing or uninstalling your suppressor, verify that the magazine is out of the firearm and that the firearm is unloaded. Failure to do so, may result in serious injury or death. Your suppressor will become hot while in use, when installing or uninstalling the suppressor use the proper protective gear. Place the suppressor in an area where it will not come in contact with flammable material. Verify bore alignment prior to use. This suppressor has caliber and barrel length restrictions, failure to follow these restrictions will void your warranty and may lead to serious injury or death.

- This suppressor must remain under 750 degrees fahrenheit.
- This suppressor is not full auto rated.
- Failure to follow barrel restrictions, and or temperature requirements will void your warranty.

---

### **Cleaning**

This suppressor features a Diamond-like-carbon outer coating and an S-line inner coating. This inner coating alleviates the need for cleaning. This coating reduces carbon fouling and improves corrosion resistance. With high pressure rifle cartridges the need for cleaning is almost non existent. At any time you question the need for the suppressor to be cleaned simply contact us and we will get you taken care of.

---

### **Barrel Restrictions**

22" – 300 RUM, 300 PRC, 300 Win mag, 7mm Mag, 6.5 PRC, 270 Win  
14.5" – .308, 6.5 Creedmoor, .243 Win  
11.5" – 5.56/223, 6.5 Grendel, 6 ARC  
7" – 300 Blackout Supersonic  
5" – 300 Blackout Subsonic

***Contact us at [info@resilientsuppressors.com](mailto:info@resilientsuppressors.com) if your caliber is not specified or you have any questions.***